

VOC Content Test Certificate

Monday, 02nd July 2018

Supplier: Trafalgar Fire Containment Solutions (26A Ferndell Street, South Granville, NSW 2142 Australia).

Sample Description: Fyrepex HP Sealant

Date Tested: 2nd July 2018 (Tested by FORAY Laboratories – NATA Accreditation 1231)


Test Method: Method 304-91 Determination of Volatile Organic Compounds (VOC) in Various Materials as referenced by South Coast Air Quality Management District (SCAQMD) Rule 1168.

Test Data:

<p>Specification</p> <p>Green Building Council of Australia Green Star Design & As Built V1.1 13.1.1 Green Star Interiors V1.1 12.1.1B</p>	<p>Fyrepex HP Sealant</p>
<p>Fire retardant sealants and adhesives: 250 grams per Litre as VOC content per material</p>	<p>7 grams per Litre as VOC content per material</p>
<p><i>We hereby certify Fyrepex HP Sealant is well below the VOC Content limits of chosen category specified by Green Star Design, Green Building Council of Australia</i></p>	



Dr. Vyt Garnys
PhD, BSc(Hons) AIMM, ARACI, ISIAQ
ACA, AIRAH, FMA
Managing Director and Principal Consultant



Tuan Duong
BE (Chem. Eng.)
Consultant



Nick Joy
BSc (Hons)
Consultant

CV180605A