

# FyreDAMPER CEILING PLENUM BOX ORDER CONFIRMATION

Clear Form

Customer to complete for each size Ceiling Plenum Box required. All dampers will be manufactured based on internal dimensions supplied by the customer within a tolerance of +/-2mm.

Frame Type	Custom Dimensions (mm)						
<p><b>(Internal view)</b></p> <p>60 mm</p> <p>Internal Width (mm)</p> <p>Internal Length (mm)</p> <p>Internal Length + 120mm</p> <p>External Width = Internal Width + 120mm</p> <p><b>(Side view)</b></p> <p>Internal Height (mm)</p> <p>External Height = Internal Height + 100mm</p>	<p><b>INTERNAL Dimensions (mm)</b></p> <table border="1"> <tr> <td>Length (Max. 1180mm)</td> <td></td> </tr> <tr> <td>Width (Max. 580mm)</td> <td></td> </tr> <tr> <td>Height (Max. 500mm)</td> <td></td> </tr> </table> <p><b>External Dimensions are:</b></p> <p><b>(Internal Width + 120mm) x</b></p> <p><b>(Internal Length + 120mm) x</b></p> <p><b>(Internal Height + 100mm)</b></p> <p><b>Internal Use Only</b></p> <p><b>Damper Size:</b></p>	Length (Max. 1180mm)		Width (Max. 580mm)		Height (Max. 500mm)	
	Length (Max. 1180mm)						
	Width (Max. 580mm)						
	Height (Max. 500mm)						

*FyreFLEX Sealant required for bedding the Plenum box to the ceiling and for sealing cable penetrations.*

*If the above does not meet your requirements, please contact our Sales Team on 1800 888 714.*

**FyreDAMPER**



Special Instructions		
Company Name		
Contact Name		
Quantity   Date		
E-mail   Phone		
Signature		
		<b>SUBMIT</b>